







# FLEX

Contemporary burn out fabric. Overlapping stripes achieve a delightful pattern on a sheer back drop. Contrast rich colours further strengthen the architectonic effect. Particularly in large window expanses the rhythmical, yet quiet arrangement is shown off to best advantage.



- Use:** Transparent curtain fabric
- Number of colours:** 6  
Special colours available from 300 m / 330 yds upwards.
- Material:** 52% Polyester  
48% Cotton
- Fabric width:** 300 cm/118 inch/3.28 yard
- Can be railroaded:** Can be railroaded
- Weight:** 36 g/m<sup>2</sup>
- Pattern repeat:** Width: 300.0 cm/118 inch/3.28 yard  
Height: 101.0 cm/40 inch/1.1 yard
- Additional use:** 
- Care:**     
- Washing (length shrinkage):** 0.5%
- Dry cleaning (length shrinkage):** 1%
- Certificates / tests:** Lightfastness certificate
- \*all testing reports can be downloaded from our website under product details
- Special notes:** - On the highly sheer base, burning out of the cotton component occasionally leaves tiny visible flecks of residue.



# FLEX



Col. 0001



Col. 0002



Col. 0003



Col. 0004



Col. 0005



Col. 0006

**Note:**

Colours may vary. Please ask for our colour samples.

\* As long as stock lasts

# CARE SYMBOLS FOR TEXTILES

## Washing (wash tub)



Normal process 95°



Mild process 95°



Normal process 60°



Mild process 60°



Normal process 40°



Mild process 40°



Very mild process 30°



Hand wash



Do not wash

The numbers in the washing tub specify the maximum temperature in °C which must not be exceeded. The bar underneath the wash tub characterizes a milder cycle with reduced mechanical action.

## Ironing (hand iron)



Iron at maximum sole-plate temperature



Iron at a medium sole-plate temperature. Take care when using a steam iron



Iron at a low sole-plate temperature. Take care when using a steam iron



Do not iron

The number of dots indicates the severity as regards to temperature of the handiron.

## Chlorine-based bleaching (triangle)



Chlorine-based bleaching allowed



Do not use chlorine-based bleach

## Tumble drying (circle in a square)



Drying at a lower temperature setting



Do not tumble dry

The numbers of dots indicates the severity as regards to temperature of the tumble drying treatment.

## Dry-cleaning (circle)



Self-service cleaning also allowed (A)



Drycleanable



Drycleanable



Self-service cleaning not allowed (F)



Self-service cleaning not allowed (F2)



Do not dry clean



Mild professional wet-cleaning

The letters within the circle specify the solvents that can be used. The bar under the circle indicates that certain limitations in the drycleaning process are required. These may concern mechanical action and/or drying temperature and/or water addition in the solvent. – No selfservice cleaning allowed.

## Gecko



















Cleaning with window wiper (Unger method)














Cleaning by "Spray Extraction" method by machine

# SYMBOLS AND PRODUCT INFORMATION

## Product information

	Inherently flame retardant
	Width (cm)
	Can be railroaded
	Has to be railroaded
	Must not be railroaded
	Pattern repeat displaced
	Repeat in warp direction
	Repeat in weft direction
	Weight (g/m <sup>2</sup> )
	Yarn dyed
	Piece dyed
	Knitted
	Woven
	Warp print
	Screen print/burnout
	Metalized on one side

	Free from harmful substances / Oddy
	Antimicrobial (counteracts colonisation and multiplying of micro organisms and odours.)
	light transmission level Tv, n-h
	light transmission level Tv, n-nn
	light transmission level Tv, n-dif
	light reflection level Pv, n-h
	light absorption level Av
	UV transmission level Tuv
	solar transmission level Te, n-h
	solar reflection level Pe, n-h
	solar absorption level Ae

## Material information

<b>AC</b>	Acetate
<b>CA</b>	Hemp
<b>CO</b>	Cotton
<b>EA</b>	Elasthan
<b>GL</b>	Glass fibre
<b>LI</b>	Linen
<b>MD</b>	Modal
<b>ME</b>	Metal
<b>PA</b>	Polyamide
<b>PC</b>	Acrylic
<b>PE</b>	Polyethylene
<b>PI</b>	Paper
<b>PL</b>	Polyester
<b>PLF</b>	Flameretardant polyester
<b>PLF CS</b>	Flameretardant polyester (Trevira CS)
<b>PN</b>	Polycarbonat
<b>PP</b>	Polypropylene
<b>PU</b>	Polyurethan
<b>RA</b>	Ramie
<b>SE</b>	Silk
<b>SI</b>	Silicone
<b>TR</b>	Different material (wood, paper, feathers etc.)
<b>VI</b>	Viscose
<b>WM</b>	Wool Mohair
<b>WV</b>	Wool

# SYMBOLS AND PRODUCT INFORMATION

## Intended purposes



Curtains/Sheers



Roller blinds (colours see separate roller blind collection)



Panels (we recommend to process the panels in warp direction to get optimal hang properties)



Vertical blinds



Roman blinds



Upholstery (for heavy use in contract application).  
Martindale > 30'000



Upholstery (for heavy use in domestic application/for normal use in contract application). 20'000 < Martindale < 30'000



Upholstery (for normal use in domestic application/for careful use in contract application). Martindale < 20'000



Loose cover for careful use in domestic application.  
Martindale < 5'000



Bedspreads



Table cloth domestic use



Wallcovering



Textile wallpaper (can be paper backed, minimum quantity)



Cushion



Acoustical fabrics



Adhesive Textiles/Gecko/Gecko in the Box



Fabrics with very high lightfastness for indoor and outdoor use



Reverso